

BROOKS

EQUIPMENT

Phone: 1300 276 657

Email: service@brooksequipment.com.au

www.brooksequipment.com.au

Brooks Equipment Sales Pty Ltd ACN 646 171 217 as trustee for Brooks Equipment Sales Trust ABN 92 455 723 027

*Quality brands
Quality products
Quality service*



“Better being with Brooks”



PERTH

30 Coulson Way
Canning Vale WA 6155

SYDNEY

3 Glossop Street
North St Marys NSW 2760

MELBOURNE

610 Geelong Road
Brooklyn VIC 3012

BRISBANE

2355 Ipswich Road
Oxley QLD 4075

ADELAIDE

525 South Street
Regency Park SA 5010

DARWIN

402 Stuart Highway
Winnellie NT 0820

BUNBURY

3 Richter Road
Davenport WA 6230

KALGOORLIE

2-4 Williams Street
West Kalgoorlie WA 6430

PORT HEDLAND

1 Manganese Street
Wedgefield WA 6721

NEWMAN

2 Bangkerbang Close
Newman WA 6753

KARRATHA

1 Coolawanyah Road
Karratha WA 6714

TOOWOOMBA

8575 Werrego Highway
Withcott QLD 4352

DALBY

172 Drayton Street
Dalby QLD 4405

MACKAY

27 Barnes Creek Road
Cremorne QLD 4740

PORT AUGUSTA

70 Victoria Parade
Port Augusta SA 5700

ALBANY

140 Chester Pass Road
Lange WA 6330



WHO ARE BROOKS EQUIPMENT?



Brooks Equipment is a part of the Brooks Hire Group, an Australian family owned and operated business since 1979. With over 40 years experience in construction machinery, we've built a solid reputation of reliability and integrity.

We specialise in the sale of new and used construction equipment.

WHAT CAN WE OFFER YOU?



QUALITY ASSURANCE

- ISO & Australian Standards in Quality Management, Health & Safety, and Environmental Management.



NEW EQUIPMENT

- Authorised dealers for Husqvarna Construction, Italdem, CompAir, and Genmac.
- Growing range of equipment such as Plate Compactors, Trench Rollers, Compressors, Rock Breakers, Light Towers, and Generators.



USED EQUIPMENT

- Large range of earthmoving equipment such as Excavators, Wheel Loaders, Tool Carriers, Dump Trucks, Graders, Smooth Drum Rollers, and Multi Tyre Rollers.
- Quality brands such as Caterpillar, Komatsu, Volvo, Hitachi, Hyundai, and Bomag.



SERVICE & PARTS

- Team of specialist Parts Interpreters with a huge range of spare parts kept in store.

TRANSPORT & DELIVERY

- 16 Branches Australia wide. Delivery can be facilitated to any jobsite in Australia.

New Equipment List

PLATE COMPACTORS



Husqvarna LF 50 L

53kg Forward Plate Compactor - Soil

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 2.1 kW
- Exhaust Emissions 976 g/kWh
- Power Fuel Type Petrol
- Frequency 95 Hz
- Speed Forward Max 0.02 km/h
- Speed 32 m/min



Husqvarna LF 60 LAT

67kg Forward Plate Compactor - Soil & Asphalt

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 2.1 kW
- Exhaust Emissions 757 g/kWh
- Power Fuel Type Petrol
- Speed Forward Max 0.03 km/h
- Speed 25 m/min



Husqvarna Lfv 80

Forward Plate Compactor

- Motor/Engine Model GX160
- Power Output
- Exhaust Emissions 757 g/kWh
- Power Fuel Type Petrol
- Sound Power Level 104 dB(A)
- Sound Pressure Level at operators ear 93 dB(A)



Husqvarna LF 80 L

84kg Forward Plate Compactor - Soil & Asphalt

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3.6 kW
- Exhaust Emissions 757 g/kWh
- Power Fuel Type Petrol
- Frequency 95 Hz
- Speed 32 m/min



Husqvarna LF 75 LAT

95kg Forward Plate Compactor - Soil & Asphalt

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3.6 kW
- Exhaust Emissions 757 g/kWh
- Power Fuel Type Petrol
- Idling Speed 1400 rpm
- Speed Forward Max 0.03 km/h
- Speed 27 m/min



Husqvarna LF 100 LAT

118kg Forward Plate Compactor - Soil & Asphalt

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3.2 kW
- Exhaust Emissions 987 g/kWh
- Power Fuel Type Diesel
- Speed 25 m/min

*Petrol option available



Husqvarna LG 164

166kg Forward & Reversible Plate Compactor - Small

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3.6 kW
- Exhaust Emissions 987 g/kWh
- Power Fuel Type Diesel
- Speed Forward Max 0.02 km/h
- Speed 32 m/min

*Petrol option available



Husqvarna LG 204

251kg Forward & Reversible Plate Compactor - Small

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3.1 kW
- Exhaust Emissions 987 g/kWh
- Power Fuel Type Diesel
- Speed 22 m/min
- Starter Electric

*Petrol option available



New Equipment List

PLATE COMPACTORS



Husqvarna LG 300

282kg Forward & Reversible Plate Compactor - Small

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 4.4 kW
- Exhaust Emissions 987 g/kWh
- Power Fuel Type Diesel
- Speed 25 m/min
- Starter Recoil

*Petrol option available



Husqvarna LG 400

436kg Forward & Reversible Plate Compactor - Medium

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 6.2 kW
- Exhaust Emissions 757 g/kWh
- Power Fuel Type Diesel
- Speed 25 m/min

*Petrol option available



Husqvarna LG 504

513kg Forward & Reversible Plate Compactor - Medium

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 9.1 kW
- Exhaust Emissions 975 g/kWh
- Power Fuel Type Diesel
- Speed 32 m/min
- Starter Recoil



Husqvarna LH 700

780kg Forward & Reversible Plate Compactor - Heavy

- Power Output 11 kW
- Exhaust Emissions 974.76 g/kWh
- Power Fuel Type Diesel
- Speed 30 m/min
- Starter Electric



Husqvarna LH 804 - Remote Control

820kg Forward & Reversible Plate Compactor - Heavy

- Power Output 11 kW
- Exhaust Emissions 974.76 g/kWh
- Power Fuel Type Diesel
- Frequency 56Hz
- Speed 30 m/min



DOUBLE DRUM ROLLERS

Husqvarna LP 6505

Weight: 765kg

- Motor/Engine Model 1D42S
- Power Output 6.8 kW
- Exhaust Emissions 993.78 g/kWh
- Power Fuel Type Diesel
- Frequency 58Hz
- Speed Forward Max 3.6km/h
- Speed 60 m/min
- Starter Electric





New Equipment List

TAMPERS



Husqvarna LT 5005

Weight: 62kg

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 2.7 kW
- Exhaust Emmissions 976 g/kWh
- Power Fuel Type Petrol
- Speed Forward Max 0.02 km/h
- Speed 16.5 m/min



Husqvarna LT 6005

Weight: 69kg

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 2.7 kW
- Exhaust Emmissions 674 g/kWh
- Power Fuel Type Petrol
- Speed Forward Max 0.02 km/h
- Speed 16.5 m/min



Husqvarna LT 8005

Weight: 62kg

- Motor/Engine Model 4 Stroke air-cooled
- Power Output 3 kW
- Exhaust Emmissions 1018 g/kWh
- Power Fuel Type Diesel
- Speed 11.5 m/min
- Plate length 330mm
- Plate width 330mm



TRENCH ROLLERS



Husqvarna LP 9505 - Remote Control

Weight: 1680kg

- | | |
|--------------------------------|------------------------------|
| ● Motor/Engine Model D1105 | ● Frequency 42Hz |
| ● Power Output 18 kW | ● Speed Forward Max 1.35km/h |
| ● Exhaust Emmissions 976 g/kWh | ● Speed 22.5 m/min |
| ● Power Fuel Type Diesel | ● Starter Electric |



The highly productive Husqvarna LP 9505 articulated trench compactor delivers a smooth, compacted surface, which doesn't dig up soil when turning. Due to the high operating weight and ultimate traction, it is suitable for all kinds of soils (dry or wet) but especially suited for cohesive materials like clay and silt. The fuel-efficient engine provides class-leading power for a whole day of uninterrupted work and the radio remote control offers great flexibility, better ergonomics and safer working conditions. Servicing is quick and easy with all service points clearly marked and easily accessed under the hoods.

New Equipment List

ROCK BREAKERS



Italdem GK 75 S

Excavator Size: 0.5 - 2 Tonne

- Operating Weight 75kg
- Tool Diameter 40mm
- Oil Flow 13 - 25 l/min
- Working Pressure 95 - 105 bar
- Relief Valve 140 bar
- Required Power 6 hp
- Impact Rate 750 - 1430



Italdem GK 100 S

Excavator Size: 1 - 3 Tonne

- Operating Weight 105kg
- Tool Diameter 46mm
- Oil Flow 15 - 30 l/min
- Working Pressure 95 - 105 bar
- Relief Valve 140 bar
- Required Power 7 hp
- Impact Rate 700 - 1350



Italdem GK 165 S

Excavator Size: 2 - 4.5 Tonne

- Operating Weight 155kg
- Tool Diameter 56mm
- Oil Flow 25 - 40 l/min
- Working Pressure 95 - 105 bar
- Relief Valve 140 bar
- Required Power 9.5 hp
- Impact Rate 670 - 1050



Italdem GK 225 S

Excavator Size: 3 - 6 Tonne

- Operating Weight 220kg
- Tool Diameter 67mm
- Oil Flow 35 - 60 l/min
- Working Pressure 95 - 105 bar
- Relief Valve 140 bar
- Required Power 14 hp
- Impact Rate 620 - 1050



Italdem GK 320 S

Excavator Size: 4.5 - 9 Tonne

- Operating Weight 330kg
- Tool Diameter 80mm
- Oil Flow 45 - 85 l/min
- Working Pressure 95 - 105 bar
- Relief Valve 140 bar
- Required Power 20 hp
- Impact Rate 540 - 1000



Italdem GK 450 S

Excavator Size: 7 - 11 Tonne

- Operating Weight 450kg
- Tool Diameter 85mm
- Oil Flow 75 - 100 l/min
- Working Pressure 105 - 115 bar
- Relief Valve 150 bar
- Required Power 25.5 hp
- Impact Rate 650 - 900



Italdem GK 630 S

Excavator Size: 9 - 15 Tonne

- Operating Weight 650kg
- Tool Diameter 105mm
- Oil Flow 110 - 130 l/min
- Working Pressure 110 - 120 bar
- Relief Valve 170 bar
- Required Power 35 hp
- Impact Rate 600 - 650



Italdem GK 1060 S

Excavator Size: 13 - 20 Tonne

- Operating Weight 1050kg
- Tool Diameter 114mm
- Oil Flow 130 - 150 l/min
- Working Pressure 110 - 120 bar
- Relief Valve 170 bar
- Required Power 38 hp
- Impact Rate 500 - 600



New Equipment List

ROCK BREAKERS



Italdem GK 1360 S

Excavator Size: 18 - 25 Tonne

- Operating Weight 1350kg
- Tool Diameter 120mm
- Oil Flow 150 - 160 l/min
- Working Pressure 140 - 150 bar
- Relief Valve 200 bar
- Required Power 50 hp
- Impact Rate 600



Italdem GK 1560 S

Excavator Size: 20 - 28 Tonne

- Operating Weight 1500kg
- Tool Diameter 132mm
- Oil Flow 160 - 170 l/min
- Working Pressure 140 - 150 bar
- Relief Valve 200 bar
- Required Power 56 hp
- Impact Rate 580



Italdem GK 1810 S

Excavator Size: 22 - 30 Tonne

- Operating Weight 1800kg
- Tool Diameter 140mm
- Oil Flow 200 - 210 l/min
- Working Pressure 140 - 150 bar
- Relief Valve 200 bar
- Required Power 70 hp
- Impact Rate 550
- Max. Noise Level 88 db-A (silenced version)



Italdem GK 2500 S

Excavator Size: 28 - 40 Tonne

- Operating Weight 2400kg
- Tool Diameter 150mm
- Oil Flow 220 - 230 l/min
- Working Pressure 140 - 150 bar
- Relief Valve 200 bar
- Required Power 78 hp
- Impact Rate 550
- Max. Noise Level 88 db-A (silenced version)



Italdem GK 3000 S

Excavator Size: 30 - 50 Tonne

- Operating Weight 3000kg
- Tool Diameter 165mm
- Oil Flow 250 - 260 l/min
- Working Pressure 150 - 160 bar
- Relief Valve 200 bar
- Required Power 93 hp
- Impact Rate 500
- Max. Noise Level 88 db-A (silenced version)



Italdem GK 4000 S

Excavator Size: 40 - 65 Tonne

- Operating Weight 4000kg
- Tool Diameter 185mm
- Oil Flow 300 - 310 l/min
- Working Pressure 150 - 160 bar
- Relief Valve 200 bar
- Required Power 112 hp
- Impact Rate 450
- Max. Noise Level 88 db-A (silenced version)



New Equipment List

GENERATORS

Genmac King G80PS

Autonomy at 75% of load 11h

- PRP Continuous Power 80 kVA
- PRP Continuous Power 64 kW
- LTP Stand-by Power 88 kVA
- LTP Stand-by Power 70 kW
- Voltage VAC 400/230
- Frequency 50 Hz
- Ampere PRP / LTP 116/127
- Speed 1500 rpm



Genmac Queen G100PS

Autonomy at 75% of load 16h

- PRP Continuous Power 100 kVA
- PRP Continuous Power 80 kW
- LTP Stand-by Power 110 kVA
- LTP Stand-by Power 88 kW
- Voltage VAC 400/230
- Frequency 50 Hz
- Ampere PRP / LTP 145/159
- Speed 1500 rpm



Genmac Strong G45PS

Autonomy at 75% of load 12h

- PRP Continuous Power 45 kVA
- PRP Continuous Power 36 kW
- LTP Stand-by Power 50 kVA
- LTP Stand-by Power 40 kW
- Voltage VAC 400/230
- Frequency 50 Hz
- Ampere PRP / LTP 65/72
- Speed 1500 rpm



LIGHTING TOWERS

Genmac Winky

- Illuminated Surface 5000 m²
- Light Type MultiLED
- Lights 4 x 320 W LED
- Lumen 166200
- Mast Hydraulic
- Mast Height Max 8.5m
- Rotation 359°
- Resistance to Wind 110 Km/h
- Base With forklift pockets
- Dimensions 120x100x230 cm
- Weight 550kg
- Galvanized telescopic mast
- Each lamp has its own On/Off switch



Genmac Bellatrix

- Illuminated Surface 4900 m²
- Lights 4 x 350 W LED
- Mast Hydraulic
- Mast Height Max 8.5m
- Rotation 350°
- Base With forklift pockets
- Fuel Diesel
- Zinc plating steel telescopic mast
- Sound-proof diesel generator with engine protection card.
- Coiled cable to power the headlights
- Slow speed single axle trailer with suspension
- Each lamp has its own On/Off switch
- Lockable doors



New Equipment List

COMPRESSORS



CompAir C50

Engine: Yanmar 4TNV88BKCP

- Engine Power 35 kW
- RPM Range 1600-2800
- Volume Flow m³/min 5.0
- Working Pressure bar 7
- Working Pressure psi 101.5
- Engine Oil 7.4 L
- Diesel Tank 60 L
- Compressor Oil 9 L



CompAir C76

Engine: Cummins B3.3 TAA

- Engine Power 63 kW
- RPM Range 1600-2600
- Volume Flow m³/min 7.6
- Working Pressure bar 7
- Working Pressure psi 101.5
- Engine Oil 8 L
- Diesel Tank 140 L
- Compressor Oil 17.5 L



CompAir C110-9

Engine: Cummins QSB 4.5

- Engine Power 97 kW
- RPM Range 1300-2300
- Volume Flow m³/min 11.3
- Working Pressure bar 8.6
- Working Pressure psi 124.7
- Engine Oil 11 L
- Diesel Tank 210 L
- Compressor Oil 24 L

