







HUSQVARNA COMPACTION EQUIPMENT

LP9505

Product Specifications

WEIGHT
1675 kg

SPEED
0 - 2.7 km / h

VIBRATING FREQUENCY
42 Hz

ENGINE POWER

18.1 kW



BOOSTING PRODUCTIVITY IN CHALLENGING TRENCHES

Husqvarna LP 9505 is a powerful, easy-to operate trench compactor, delivering superb productivity in demanding trench compaction jobs. Whether steep, tight or loose soils, LP 9505 will get the job done on time. The high operating weight enables efficient compaction without vibration, from the initial static passes all the way to the finish.

The reliable, fuel-efficient Kubota diesel engine is Tier 4 Final compliant and provides class-leading power, while the articulated steering allows the compactor to turn corners without digging up the soil. The extra high and wide drum pads are optimally designed to make sure you have the traction to handle your daily tasks in wet or dry cohesive soils.

Husqvarna LP 9505 features a wealth of smartly designed solutions, which enable the operator to perform at his/her best.

The durable remote control is lightweight and designed for smooth, safe maneuvering with distinct drivability and feel, even with working gloves on. The control display alerts the operator when something needs to be checked.

Radio remote control technology enables the operator to choose the standing position that will produce the best end result. This provides better ergonomics and safer working conditions. The wide drums and low center of gravity deliver excellent stability to increase safety even further. Servicing is quick and easy with all service points clearly marked and easily accessible under the protective hoods.







www.brooksequipment.com.au



TRENCH COMPACTORS



EASY LOADING AND TRANSPORTING

LP 9505 features a single lifting point with a large lifting eye. The articulation joint is secured with a foldable transport lock. There are also eyelets in the front and back end for hauling.

SERVICE MADE OUICK AND EASY

All service points are easily accessible under the hoods. The filters, hydraulic hoses and other components are clearly marked with article numbers to facilitate the ordering of spare parts – no need to look up the manual.

FILLED UP FOR PRODUCTIVITY

The 30-liter fuel tank allows for a class-leading 8.6 hours of uninterrupted work.

HUSQVARNA LP 9505



OPTIMAL TRACTION AND COMPACTION

The drum pads are optimally designed and sized for best possible traction. The drum end covers provide extra protection for the hub sealings and slide against the trench walls instead of grinding them. The optional drum width extensions are easy to mount.



ON-BOARD BATTERY STATION AND STORAGE COMPARTMENT

A lockable compartment is integrated into the hood, providing storage for the remote and on-board charging of the second battery. Furthermore, you can connect or charge accessories with the 12 V power outlet (e.g. working lights).



The modern remote control is designed with top-class ergonomics and drivability in mind. The display keeps the operator in continuous control of machine status and alerts.



1300 BROOKS (276 657)

service@brooksequipment.com.au

www.brooksequipment.com.au



FORWARD AND REVERSIBLE PLATE COMPACTORS – LG SERIES SMALL

















A 1 10 P 2 1 1 15 20				LG 300					LG 204				LG 164		
Engine	Honda GX270	Honda GX270	Hatz 1B30	Hatz 1B30	Hatz 1B30	Hatz 1B30	Honda GX200	Hatz 1B20	Hatz 1B20	Hatz 1B20	Honda GX160	Honda GX160	Hatz 1B20	Hatz 1B20	Hatz 1B20
Power, kW	5.3	5.3	4.7	4.7	4.7	4.7	4.1	3.1	3.1	3.1	3.6	3.6	3.1	3.1	3.1
Fuel	Petrol	Petrol	Diesel	Diesel	Diesel	Diesel	Petrol	Diesel	Diesel	Diesel	Petrol	Petrol	Diesel	Diesel	Diesel
Operating weight, kg	270	265	287	282	307	302	211	228	251	244	157	148	185	170	166
Frequency, Hz	68	68	68	68	68	68	65	65	65	65	80	80	80	80	80
Centrifugal force, kN	40	40	40	40	40	40	36	36	36	36	28	28	28	28	28
Speed, n/min	25	25	25	25	25	25	23	22	22	22	22	22	22	22	22
H/A handle vibrations m/s ²	2.4	2.4	1.7	1.7	1.7	1.7	3.5	2.8	2.8	3.4	2.3	2.3	2.8	3.5	3.2
Sound power, guaranteed, LWA, dB(A)	108	108	108	108	108	108	106	108	108	108	108	108	108	108	108
Sound pressure at operators ear, LWA, dB(A)	95	95	95	95	95	95	84	93	93	85.1	82.4	81.9	93	84	84.1
Plate width, mm	600	500	600	500	600	500	500	500	600	500	450	350	600	450	350
L×W×H, mm	1385×600×1120	1385×500×1120	1385×600×1120	1385×500×1120	1385×600×1120	1385×500×1120	1334×500×1126	1334×500×1126	1334×600×1126	1334×500×1126	119×450×1069	119×350×1069	119×600×1069	119×450× 1069	119×350×1069
PART NUMBERS			The same												
Manual start	967 85 53-02	967 85 53-01	967 85 53-05	967 85 53-04		- 2 - 700	967 85 52-01	967 85 52-05			967 85 56-01	967 85 56-02	967 89 76-04	967 89 76-02	967 89 76-01
Electric start				200	967 85 53-06	967 85 53-07			967 85 52-03	967 85 52-06	-		-		

ACCESSORIES/OPTIONAL	10 FE 160			LG 300	E E PORTO	1 12 6	7 300		LG 204		6 A 100	1000	LG 164	30,300	- 14 - 32
Block paving kit	594 83 03-01	594 83 02-01	594 83 03-01	594 83 02-01	594 83 03-01	594 83 02-01	594 82 58-01	594 82 58-01	594 75 96-01	594 82 58-01	594 83 01-01	595 36 85-01	594 75 95-01	594 83 01-01	595 36 85-01
Transport device	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01	594 83 05-01

FORWARD AND REVERSIBLE PLATE COMPACTORS – LG SERIES MEDIUM









The second state of the second		LG 504			LG 400
Engine	Hatz 1D81Z	Hatz 1D81Z	Hatz 1D81Z	Honda GX 390	Lombardini 15LD 440/S (Kohler)
Power, kW	9.2	9.2	9.2	8.3	6.2
Fuel	Diesel	Diesel	Diesel	Petrol	Diesel
Operating weight, kg	513	499	470	398	436
Frequency, Hz	69	69	69	60	60
Centrifugal force, kN	65	65	65	52	52
Speed, m/min	32	32	32	25	25
H/A handle vibrations m/s ²	2.5	2.5	2.5	2.5	2.1
Sound power, guaranteed, LWA, dB(A)	_	109		108	108
Sound pressure at operators ear, LPA, dB(A)	98	98	98	95	93
Plate width, mm	850 (550+2×150)	700 (550+2×75)	550	650	650
L×W×H, mm	1670×850×1190	1670×750×1190	1670×550×1190	1690×650×1150	1690×650×1150
PART NUMBERS					
Manual start	967 85 55–10	967 85 55-09	967 85 55-08	967 85 54-01	V-10-10-10-10-10-10-10-10-10-10-10-10-10-
Electric start	967 85 55–11	967 85 55-07	967 85 55-06	10年11月	967 89 64-03
Electric start and compaction indicator	967 85 55–12	967 85 55-05	967 85 55-04		967 89 64-01

ACCESSORIES/OPTIONAL		LG 504	LG 400				
Extension plate kit 2×75 mm	594 75 87-01	594 75 87-01	594 75 87-01				
Extension plate kit 2×150 mm	594 75 88-01	594 75 88-01	594 75 88-01				
Block paving kit		595 12 89-01		594 44 79-02	594 44 79-02		

DOUBLE DRUM ROLLERS







	LP 9505	The state of the s	P 7505	LP 6505		
Engine	Kubota D1105	Hatz 1D50S	Hatz 1D50S	Hatz 1D42S	Hatz 1D42S	
Power, kW	18.1	7.9	7.9	7.2	7.2	
Fuel	Diesel	Diesel	Diesel	Diesel	Diesel	
Operating weight, kg	1675	981	1001	745	765	
Frequency, Hz	42	57	57	58	58	
Centrifugal force, kN	72/36 (high/low)	27	27	22	22	
Speed, forward / reverse, km/h	0-2.7	0-3.6	0-3.6	0-3.6	0-3.6	
H/A handle vibrations m/s ²	N/A	2.6	2.6	4.1	4.1	
Sound power, guaranteed, dB(A)	106	107	107	107	107	
Sound pressure at operators ear, dB(A)	N/A	88	88	88	88	
Drum diameter, mm	523	400	400	400	400	
Drum width, mm	850	750	750	650	650	
L×W×H, mm	1856×850×1369	1110/2500×820×1260	1110/2500×820×1260	1110/2500×720×1215	1110/2500×720×1215	
ART NUMBERS		- Jet . 1				
Manual start		967 89 74-01		967 85 57-02	三年(人) 医遗传的	
Electric start	967 95 08-01		967 89 74-02	2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	967 85 57-03	

ACCESSORIES/ OPTIONAL	LP 9505		LP 7505		LP 6505
Safety crank handle kit		594 17 09-01	594 17 09-01	594 17 09-01	594 17 09-01





