



POWER MEETS PRECISION

MADE FOR AUSTRALIAN CONDITIONS



TELESCOPIC BOOM LIFT **XGS22K**

Product Specifications

OPERATING WEIGHT
12,460 kg

RATED POWER
36 kW / 2600 rpm

WORKING HEIGHT
22 m

ENGINE
Kubota V2403BM

XGS22K

Telescopic Boom Lift

DIMENSIONS & SPECIFICATIONS



Scan to view the XGS22K product brochure

MAIN SPECIFICATIONS

POWER SOURCE

Engine Type	Kubota V2403BM-DI-CTO4e (Stage III)
Engine Power Rating	36 kW @ 2600 rpm
Power Source	12V DC proportional control

WEIGHT

Total Machine Weight	12,460 kg
----------------------	-----------

TYRES

Tyre Specifications	36x14-20; 355/55D625
---------------------	----------------------

DIMENSIONS

Overall Length		
a	Stowed, in Operation	10.08 m
	Transport, Short Arm Folded Down	9.85 m
b	Overall Width	2.49 m
c	Overall Height	2.53 m
d	Wheelbase	2.5 m
	Platform Size	2440 mm x 900 mm x 1150 mm
	Min. Ground Clearance	230 mm
	Max. Tail Swing (Stowed)	1310 mm
	Turning Radius	
	Inside	3.28 m
	Outside	6 m

FLUID CAPACITIES

Fuel Tank Capacity	150 L
Hydraulic Tank Capacity	120 L

WORKING SCOPE

Max. Working Height	22 m
Max. Platform Height	20 m
Horizontal Reach / Working Radius	17.2 m
Load Capacity of Extended Platform	300 / 460 kg (Limited)
Boom Luffing Range	-3° to +73°
Fly Jib Luffing Range	-65° to +70°
Turntable Rotation Angle	360°
Platform Rotation Angle	160°
Max. Travel Speed	
Stowed	6.3 km/h
Extended	0.6 km/h
Max. Gradeability:	
Counterweight End Up	45% (24°)
Counterweight End Down	30% (17°)

WORK CURVE GRAPH

