







DX120

**Product Specifications** 

OPERATING WEIGHT

2,700 kg

RATED POWER

33 HP

DRUM WIDTH

1,200 MM

ENGINE

KUBOTA





### PERFORMANCE, RELIABILITY & VALUE

#### **KUBOTA ENGINE**

Featuring a choice of 2 engines, the Tier 3 Kubota D1703 or the D1803-CR-E5B, 33 HP, 24.6 kW water-cooled, 3 cylinder engine with high power reserve, low fuel consumption and low noise emission.

#### **HEAVY DUTY DRUM**

Inner-cylinder drum chamber is simple and robust for excellent performance, long lifetime and exceptionally high reliability.

#### COMPACTION

The XD120 has a large diameter drum with two vibration frequencies available, also included is pressurised, interval water spray help the operator get the job done quicker with less tools.

#### **PREMIUM GRADEABILITY**

Proportional ASC closed loop hydraulic drive system composed of a variable displacement pump, plus a constant motor. Drum selection is made easy with a switch for front, rear or both.

#### **MANOEUVRABILITY**

The XD120 features high transport speed, narrow turning radius and high level gradability, made possible by the closed loop hydraulic propel system.

#### **SAFETY**

Safety features of the XD120 include e-stop switch, seat occupation switch and seat belt, helping make the work area. The battery is fitted with an isolator under the hood.















### XD120

#### **COMFORTABLE**

Ergonomic setup with comfortable seat, foldable ROPS, multifunction travel control lever, plus easy access to vibration control, horn and spray override.

#### **EFFICIENT MAINTENANCE**

Engine hood tilts forward easily and extensively for better access to service and maintenance areas and all fundamental componentry.

#### **EXCELLENT VISIBILITY**

The seat position provides the operator excellent drum edge visibility, as well as an easy view of the rear drum. Plus the LED worklights allow better visibility in low light situations.

#### **GLOBAL DOMINANCE**

XCMG is the World's 3rd largest construction machinery manufacturer, with branches dealers and service agents throughout Australia.

#### **RELIABILITY & TRUST**

XCMG's key focus is the complete satisfaction and success of every machine owner - making your business as profitable as possible.

#### **UNMATCHED SUPPORT**

Product experts at your local dealer provide exceptional support throughout your machine's lifetime: operation, maintenance and service from the delivery date through to its last day on the job.















# **XD120**








- 1300 BROOKS (276 657)
- @ sales@brooksequipment.com.au
- www.brooksequipment.com.au





## **XD120**






- 1300 BROOKS (276 657)
- @ sales@brooksequipment.com.au
- www.brooksequipment.com.au









Dimensions (mm)	A	В	С	D	E	F	G	н	1	K
XD120	2565	1286	2575	275	1200	1773	42	1845	11	720

Item	Content	Unit	XD120		
Parameters	Operating Weight:	kg	2700		
	Static Load Front Drum:	N/cm	110		
	Static Load Rear Drum:	N/cm	110		
	Amplitude:	mm	0, 5		
	Frequency:	Hz	63/67		
	Vibration Force:	kN	36/41		
	Drum Dimensions:	mm	720x1200		
Propel Performance	Speed:	km/h	0-10		
	Gradeability:	%	30		
	Minimum Turning Radius - Inner:	mm	2250		
	Minimum Turning Radius - Outer:	mm	3450		
	Oscillation Angle:	0	±8		
	Engine Manufacturer:		Kubota		
	Type:		D1803-CR-E5B or D1703		
	Cooling:		Water		
Engine Chase	Emission Stage:		Tier 3 or Tier 5		
Engine Specs	Number of Cylinder:		3		
	Performance I30 14390:	kW	24		
	Performance SAE J 1995:	hp	33		
	Rated Engine Speed:	min-1	2400		



- 1300 BROOKS (276 657)
- @ sales@brooksequipment.com.au
- www.brooksequipment.com.au

